





Bramall Construction and Frank Haslam Milan are Keepmoat companies

### WORKSHOP

### MECHANICAL AND ELECTRICAL SERVICES EARLY DESIGN DEVELOPMENT AREAS TO FOCUS ON AND ANY ASSOCIATED COMPLIANCE CHANGES TO BE AWARE OF


### FIRE SAFETY DESIGN IN EXTRA CARE

















### DEREK GRIFFITHS MANAGING DIRECTOR/CHARTERED ENGINEER

### **BES Consulting Engineers Limited**

 Mechanical and Electrical Building Services Consultants/Designers (based in County Durham and Slough)



### DEREK GRIFFITHS MANAGING DIRECTOR/CHARTERED ENGINEER

### **BES Consulting Engineers Limited**

- Mechanical and Electrical Building Services Consultants/Designers (based in County Durham and Slough)
- Extensive experience of design/project delivery in relation to Elderly Extra Care Projects:

Numerous project involvement over the past 12 years in Extra Care and previously Sheltered Housing



 Some of the Clients we have worked with to deliver Extra Care Developments :



 Some of the Clients we have worked with to deliver Extra Care Developments:

> **Hanover** (Nationally) **Sanctuary** (Nationally) **Anchor Trust** (Nationally) **Abbeyfield** (Yorkshire) **Joseph Rowntree** (Yorkshire) **Tees Valley/Fabrick Group** (North East) **Eden Housing Association** (Cumbria) **Places for People** (North East/Yorkshire) Yorkshire Housing South Yorkshire Housing **Home Group** (North East) **Endeavour Housing (North East)** Milecastle Housing (North East)



## EARLY INVOLVEMENT OF M&E CONSULTANCY DESIGN ADVICE IS VITAL TO SUCCESSFUL PROJECT DELIVERY



## EARLY INVOLVEMENT OF M&E CONSULTANCY DESIGN ADVICE IS VITAL TO SUCCESSFUL PROJECT DELIVERY

### MINIMISE YOUR RISKS AT DESIGN AND BUILD TENDER STAGE



## EARLY INVOLVEMENT OF M&E CONSULTANCY DESIGN ADVICE IS VITAL TO SUCCESSFUL PROJECT DELIVERY

MINIMISE YOUR RISKS AT DESIGN AND BUILD TENDER STAGE

A QUOTE FROM NUMEROUS CLIENTS/ CONSTRUCTION PROFESSIONALS AND CONTRACTORS

"THE M&E SERVICES ON EXTRA CARE PROJECTS ARE HIGHLY COMPLEX, STRATEGIES NEED TO BE DEVELOPED AT AN EARLY STAGE – IF THE M&E SERVICES DO NOT DELIVER THE SCHEME DOES NOT DELIVER."



 On many occasions after completion we have been brought in by Clients to sort out problems on projects where we have not previously been involved.



- On many occasions after completion we have been brought in by Clients to sort out problems on projects where we have not previously been involved.
- More work in the initial planning stage usually pays dividends in delivering a quality end product.



# PARTICULAR ISSUES REQUIRING EARLY CONSIDERATION IN THE DESIGN DEVELOPMENT PROCESS (PRE-PLANNING)

 BREEAM/Code for Sustainable Homes Compliance (requirement/ standard to be achieved usually prescribed by funding bodies/ Local Authorities as part of the planning conditions).



# PARTICULAR ISSUES REQUIRING EARLY CONSIDERATION IN THE DESIGN DEVELOPMENT PROCESS (PRE-PLANNING)

 BREEAM/Code for Sustainable Homes Compliance (requirement/ standard to be achieved usually prescribed by funding bodies/ Local Authorities as part of the planning conditions).

BREEAM Multi-residential is intended for use on multi-occupancy residential buildings which are not suitable for assessment under the Code for Sustainable Homes (CSH).

Applicable to multi-residential buildings which contain a mix of residential accommodation with communal areas which make up more than 10% of the total Net Internal Floor area ie. generally Extra Care developments.













But you may also be required to assess the self-contained dwellings via the CSH assessment and provide appropriate certification.



But you may also be required to assess the self-contained dwellings via the CSH assessment and provide appropriate certification.

You need to establish the compliance requirements and applicable ratings ie. BREEAM Excellent/Very Good and CSH Level early in initial design development process to ensure the scheme is designed to meet these compliance requirements.



But you may also be required to assess the self-contained dwellings via the CSH assessment and provide appropriate certification.

You need to establish the compliance requirements and applicable ratings ie. BREEAM Excellent/Very Good and CSH Level early in initial design development process to ensure the scheme is designed to meet these compliance requirements.

Undertake very early preliminary assessment, which will assist and guide the initial design development process.



Local Authority Planning requirements in respect of renewable energy contribution obligations:

- Some LA's stipulate that a percentage of the predicted energy requirement of the development be produced by the installation of low/zero carbon technology.
- Others stipulate that the predicted carbon dioxide production of the development be reduced by a percentage by the installation of low/zero carbon technology.



- Local Authority Planning requirements in respect of renewable energy contribution obligations:
  - Some Local Authorities are requiring 20% (particularly London, others ranging from 10 20%, reduction in CO<sub>2</sub>) by use of renewables (you need to consider how you are going to achieve this at the pre-planning stage as this could have a major impact on scheme design/project costs).

- Some LA's stipulate that a percentage of the predicted energy requirement of the development be produced by the installation of low/zero carbon technology.
- Others stipulate that the predicted carbon dioxide production of the development be reduced by a percentage by the installation of low/zero carbon technology.



- Local Authority Planning requirements in respect of renewable energy contribution obligations:
  - Some Local Authorities are requiring 20% (particularly London, others ranging from 10 20%, reduction in CO<sub>2</sub>) by use of renewables (you need to consider how you are going to achieve this at the pre-planning stage as this could have a major impact on scheme design/project costs).

Sustainable energy policies can vary from one local authority to the next.

- Some LA's stipulate that a percentage of the predicted energy requirement of the development be produced by the installation of low/zero carbon technology.
- Others stipulate that the predicted carbon dioxide production of the development be reduced by a percentage by the installation of low/zero carbon technology.







There are some subtle differences in the compliance criteria in respect of energy usage and carbon reductions.



There are some subtle differences in the compliance criteria in respect of energy usage and carbon reductions.

 CSH will require a percentage reduction in CO<sub>2</sub> emissions for the dwellings generally.



There are some subtle differences in the compliance criteria in respect of energy usage and carbon reductions.

- CSH will require a percentage reduction in CO<sub>2</sub> emissions for the dwellings generally.
- BREEAM will require a percentage of reduction in CO<sub>2</sub> for the development as a whole by use of renewable energy technologies.







For example, a policy directed at the reduction of carbon dioxide will favour those LZC technologies which offset the use of grid supplied electricity. This is due to the high carbon density of grid supplied electricity ie. photovoltaics.



For example, a policy directed at the reduction of carbon dioxide will favour those LZC technologies which offset the use of grid supplied electricity. This is due to the high carbon density of grid supplied electricity ie. photovoltaics.

Generally LA's are becoming more concerned with the reduction of carbon dioxide rather than production of energy. This was demonstrated when the London plan was amended from its original position of 10% production of predicted energy generation.

The London plan now stipulates that all developments shall achieve a reduction in carbon dioxide emissions of 20% from on site renewable generation.



For example, a policy directed at the reduction of carbon dioxide will favour those LZC technologies which offset the use of grid supplied electricity. This is due to the high carbon density of grid supplied electricity ie. photovoltaics.

Generally LA's are becoming more concerned with the reduction of carbon dioxide rather than production of energy. This was demonstrated when the London plan was amended from its original position of 10% production of predicted energy generation.

The London plan now stipulates that all developments shall achieve a reduction in carbon dioxide emissions of 20% from on site renewable generation.

This is normally the target set for all of the London boroughs. Outside of the London boroughs the targets vary around the country.



Typical renewable/LZC technologies (in our experience) being utilised in Extra Care :



Typical renewable/LZC technologies (in our experience) being utilised in Extra Care :

- Ground source/air source heat pumps
- Solar photovoltaics
- Solar hot water
- Combined heat and power (CHP)
- Biomass boilers

other technologies considered

- Wind turbines
- Small scale hydro



Typical renewable/LZC technologies (in our experience) being utilised in Extra Care :

- Ground source/air source heat pumps
- Solar photovoltaics
- Solar hot water
- Combined heat and power (CHP)
- Biomass boilers

other technologies considered

- Wind turbines
- Small scale hydro

What you also need to investigate/consider, is the renewable technology proposed likely to be eligible for Government assistance in the form of Feed in Tariffs (FITs)or the new proposed Renewable Heat Incentive Tariff scheme.

It has recently come to our attention that projects receiving HCA funding may not be eligible participate in the Governments FITs programme.



 2010 Building Regulations (Part L Relating to Energy Consumed in Buildings) – Part of the implementation of the UK Low Carbon Transition Plan



- 2010 Building Regulations (Part L Relating to Energy Consumed in Buildings) – Part of the implementation of the UK Low Carbon Transition Plan
  - Requirement for improvement in energy efficiency standards by 25% by reducing CO<sub>2</sub> emissions from a base level of 2006 Part L Building Regulations.



- 2010 Building Regulations (Part L Relating to Energy Consumed in Buildings) – Part of the implementation of the UK Low Carbon Transition Plan
  - Requirement for improvement in energy efficiency standards by 25% by reducing CO<sub>2</sub> emissions from a base level of 2006 Part L Building Regulations.

A significant step towards "zero carbon" for new non domestic buildings.



- 2010 Building Regulations (Part L Relating to Energy Consumed in Buildings) – Part of the implementation of the UK Low Carbon Transition Plan
  - Requirement for improvement in energy efficiency standards by 25% by reducing CO<sub>2</sub> emissions from a base level of 2006 Part L Building Regulations.

A significant step towards "zero carbon" for new non domestic buildings.

Some other important changes to note:



- 2010 Building Regulations (Part L Relating to Energy Consumed in Buildings) – Part of the implementation of the UK Low Carbon Transition Plan
  - Requirement for improvement in energy efficiency standards by 25% by reducing CO<sub>2</sub> emissions from a base level of 2006 Part L Building Regulations.

A significant step towards "zero carbon" for new non domestic buildings.

Some other important changes to note:

Significant improvements in 'U' values are required to roofs, walls, floors and windows/doors to achieve compliance prior to introduction of renewable technologies, to meet the recognised methods of achieving compliance criteria for SBEM (Simplified Building Energy Model) and SAP (Standard Assessment Procedure) calculations.



 Significant improvements in minimum standards for internal lighting, requiring careful selection and design of lighting systems :

Type of Lighting	2006	2010	% Improvement
High occupancy areas : office, kitchens, corridors, etc	40 luminaires lumens per circuit Watt	55 luminaires lumens per circuit Watt	37.5%
Low occupancy areas : stores, plant rooms, etc.	40 lamp lumens per circuit Watt	55 lamp lumens per circuit Watt	37.5%
Display lighting	20 lamp lumens per circuit Watt	22 lamp lumens per circuit Watt	10%



 Significant improvements in minimum standards for internal lighting, requiring careful selection and design of lighting systems :

Type of Lighting	2006	2010	% Improvement
High occupancy areas : office, kitchens, corridors, etc	40 luminaires lumens per circuit Watt	55 luminaires lumens per circuit Watt	37.5%
Low occupancy areas : stores, plant rooms, etc.	40 lamp lumens per circuit Watt	55 lamp lumens per circuit Watt	37.5%
Display lighting	20 lamp lumens per circuit Watt	22 lamp lumens per circuit Watt	10%

Note: Luminaire lumens per circuit Watt takes into account how good the light fitting is at transmitting the light created by the lamp.



 Requirement for automatic meter reading, of at least 90% of the estimated annual energy consumption of each fuel to be assigned to the various end-use categories (heating, lighting, etc.) if:



 Requirement for automatic meter reading, of at least 90% of the estimated annual energy consumption of each fuel to be assigned to the various end-use categories (heating, lighting, etc.) if:

The building total communal areas exceed 1000m<sup>2</sup> (may be applicable to large Extra Care developments)



 Requirement for automatic meter reading, of at least 90% of the estimated annual energy consumption of each fuel to be assigned to the various end-use categories (heating, lighting, etc.) if:

The building total communal areas exceed 1000m<sup>2</sup> (may be applicable to large Extra Care developments)

Generally this means sub-metering the following:

Gas – incoming meter, heating, hot water (if separate gas fired water heaters), kitchen, laundry, etc.

Electricity – Incoming meter, lighting and power separately by floor, external lighting, mechanical plant, laundry, kitchen, etc.



Investigate statutory services implications : ie. gas, water electricity, telecoms.



- Investigate statutory services implications : ie. gas, water electricity, telecoms.
  - Ascertain if there are any cross-site services that may require diverting, etc.



- Investigate statutory services implications: ie. gas, water electricity, telecoms.
  - Ascertain if there are any cross-site services that may require diverting, etc.
  - Undertake preliminary load assessments for your development



- Investigate statutory services implications : ie. gas, water electricity, telecoms.
  - Ascertain if there are any cross-site services that may require diverting, etc.
  - Undertake preliminary load assessments for your development
  - Obtain preliminary proposals/budget quotations for new supplies to the development



- Investigate statutory services implications : ie. gas, water electricity, telecoms.
  - Ascertain if there are any cross-site services that may require diverting, etc.
  - Undertake preliminary load assessments for your development
  - Obtain preliminary proposals/budget quotations for new supplies to the development

This will provide information with regard to the extent of any off/ on site infrastructure implications, which could be significant if for example an electricity sub-station requires upgrading, etc. with obvious serious potential cost implications.



 Review and assess the initial architectural sketch proposals:



Review and assess the initial architectural sketch

proposals:

— Are plant areas in the correct locations and of sufficient size/area.



- Review and assess the initial architectural sketch proposals:
  - Are plant areas in the correct locations and of sufficient size/area.
  - How easily can you incorporate cost effective renewables obligations.



- Review and assess the initial architectural sketch proposals:
  - Are plant areas in the correct locations and of sufficient size/area.
  - How easily can you incorporate cost effective renewables obligations.
  - How will the services distribution strategies be accommodated (consider requirement for space for significant service risers).



- Review and assess the initial architectural sketch proposals:
  - Are plant areas in the correct locations and of sufficient size/area.
  - How easily can you incorporate cost effective renewables obligations.
  - How will the services distribution strategies be accommodated (consider requirement for space for significant service risers).
  - Could there be problems of over-heating/lack of ventilation in corridors.



- Review and assess the initial architectural sketch proposals:
  - Are plant areas in the correct locations and of sufficient size/area.
  - How easily can you incorporate cost effective renewables obligations.
  - How will the services distribution strategies be accommodated (consider requirement for space for significant service risers).
  - Could there be problems of over-heating/lack of ventilation in corridors.
  - Will there be a requirement to introduce mechanical ventilation plant/systems ie. Internal rooms with no windows and/or basement rooms.



- Review and assess the initial architectural sketch proposals:
  - Are plant areas in the correct locations and of sufficient size/area.
  - How easily can you incorporate cost effective renewables obligations.
  - How will the services distribution strategies be accommodated (consider requirement for space for significant service risers).
  - Could there be problems of over-heating/lack of ventilation in corridors.
  - Will there be a requirement to introduce mechanical ventilation plant/systems ie. Internal rooms with no windows and/or basement rooms.
  - How can fire detection/suppression systems be incorporated consider plant locations and distribution of potentially large bore pipework, storage tanks, etc.



 Review requirements for inclusion of fire suppression systems ie. sprinklers/misting system



- Review requirements for inclusion of fire suppression systems ie. sprinklers/misting system
  - Is this a requirement in respect of Building Regulations and/or specific buildings insurance requirements, etc.





COSTS



- COSTS
  - BUILDABILITY



- COSTS
  - BUILDABILITY
  - STATUTORY COMPLIANCE